

LUPI AUGUSTO TANK & PIPING PRODUCTS ITALY phone: +39 069370701 fax: +39 0697847415

e-mail: info@lupiaugusto.com lupiaugusto@tiscali.it website www.lupiaugusto.com


Technical data	
Design pressure	0.5 Bar
Design temperature	-10/+120 °C
Setting range:	
-pressure	20...1000 mmH2O
Atex certificate	
Factory tested	body pressure 0.7 Bar dimensions correct setting leakage API2521
Size/s	from 2"x3" to 12"x14"
Connections	ANSI 150# FF or UNI PN 10/16 FF
External finiture	aluminium paint as std or epoxy paint RAL7023

Dimensions and weights				
DN (xx)	Dimensions (mm)			Weight (kg)
	A	B	H	
2"x3"	203	200	290	10
3"x4"	235	229	324	16
4"x6"	265	285	410	20
6"x8"	323	343	471	27
8"x10"	700	406	600	34
10"x12 "	830	483	800	48
12"x14 "	900	534	900	63

Materials and product codes for Fig.304.1 Pressure Relief Valves, flgd discharge				
Items	Description	Materials		
2	Conveyor	Aluminium	Aluminium	Alum/PTFE lined
3	Nozzle	Aluminium	Aluminium	Alum/PTFE lined
5	Cover	Aluminium	Aluminium	Alum/PTFE lined
13	Body screws	SS304	SS304	SS316
20	Seat	Aluminium	Alum/PTFE lined	Alum/PTFE lined
32	Pallet stem	SS304	SS304	SS316
34	Guide post	SS304	SS304	SS316
35	Pallet	SS316	SS316	SS316
50	Insert	Neoprene® Viton® Teflon® Teflon® FEP Kalrez®		
60	Body gasket	Asbestos free	Asbestos free	PTFE
65	Flange gasket	Asbestos free	Asbestos free	PTFE
70	Setting weight	Lead	Lead	SS304
Product code with ANSI flange/s		303.1.xx.101	303.1.xx.103	303.1.xx.105
Product code with UNI flange/s		303.1.xx.102	303.2.xx.104	303.1.xx.106

3

FIG.304.1 PRESSURE RELIEF VALVE, FLANGED DISCHARGE



LUPI AUGUSTO TANK & PIPING PRODUCTS ITALY phone: +39 069370701 fax: +39
0697847415

e-mail: info@lupiaugusto.com lupiaugusto@tiscali.it website www.lupiaugusto.com

Neoprene® Viton® Teflon® Teflon®FEP Kalrez® are DuPont's™ trademarks. DuPont™ is a trademark of DuPont™ and its affiliates.