



LUPI AUGUSTO TANK & PIPING PRODUCTS ITALY phone: +39 069370701 fax: +39 0697847415

e-mail: info@lupiaugusto.com lupiaugusto@tiscali.it website: www.lupiaugusto.com

Technical data

Design code	ASME VIII, IX
Design pressure	5 Bar
Design temperature	-20/+120 °C
Standard features	Bidirectional seals
ATEX certified	
PED certified	
Factory tested	Dimensional Pressure 10 Bar Penetrant liquids Torque force
Sizes	From 2" to 6"
Connections	ANSI 150# FF or
External finiture:	SA 2.5 + I.Z.

Dimensions and weights

DN (xx)	Dimensions (mm)		Weight (kg)
	A	B	
2"	225	117	10
3"	296	148	18
4"	355	180	28
6"	525	244	62

Materials and product codes for Fig.601.1 Swivel joints

Items	Description	Materials
1	W.N. flanges	A105
2	90° elbows	WCB
3	Female joint element	Carbon steel
4	Screws	SS
5	Male joint elements	Carbon steel
6	Balls	Aisi 1085
7	Greaser	Galvanized steel
8	Seals	Neoprene®
9	O-ring	Buna-n
10	Label	SS304

Product code with ANSI flanges 601.1.xx.101

Neoprene® Viton® Teflon® Teflon®FEP Kalrez® are DuPont's™ trademarks. DuPont™ is a trademark of DuPont™ and its affiliates.