



LUPI AUGUSTO TANK & PIPING PRODUCTS ITALY phone: +39 069370701 fax: +39 0697847415

e-mails: info@lupiaugusto.com lupiaugusto@tiscali.it web-site : www.lupiaugusto.com

Technical data	
Design code	ASME VIII, IX
Design pressure	5 Bar
Design temperature	-20/+120 °C
Standard features	Double valves, self draining, no-freezing performance, padlock for handwheel
ATEX certified	
PED certified	
Factory tested	Dimensional pressure test 10 Bar
Sizes	3"x4" and 4"x6"
Tank connection	Flanged ANSI 150# RF
Drip connection	Treaded ANSI B2.1
External finiture	Epoxy RAL7023

Dimensions and weights					
DN (xx)	Dimensions (mm)				Weight (kg)
	A	B	C	D	
3"	3" ANSI B2.1	4" ANSI 150# RF	138	470	25
4"	4" ANSI B2.1	6" ANSI 150# RF	138	470	30

Materials and product codes for Fig.605.1 Draining valve			
Items	Description	Materials of construction	
1	Handwheel	Metal/Plastic	Metal/Plastic
2	Seals	Neoprene®	Neoprene®
3	Body	Carbon steel	Carbon steel
4	Shaft	SS316	SS316
5	External seat	Bronze	SS316
6	External valve	Bronze	SS316
7	External seal	Teflon®	Teflon®
8	Flange	Carbon steel	Carbon steel
9	Internal pipe	Carbon steel	Carbon steel
10	Spring	Carbon steel	Carbon steel
11	Internal seat	Bronze	SS316
12	Internal valve	Bronze	SS316
13	Internal seal	Teflon®	Teflon®
14	Label	SS304	SS304
Product code with Ansi flanges		605.1.xx.101	605.1.xx.103

Neoprene® Viton® Teflon® Kalrez® are DuPont's™ trademarks. DuPont is a trademark of DuPont and its affiliates